



## SPECS

TECNOLOGIA IBRIDA	
MOTORE	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus
BATTERIA	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Balsam Green
TELAIO	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORCELLA	SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
AMMORTIZZATORE	RockShox Monarch R, High Volume, 184x44mm, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Connect TR Riser 31.8x780mm
ATTACCO MANUBRIO	Giant Contact
TUBOSELLA	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SELLA	Giant Sport
PEDALI	Aluminum Platform
SISTEMA DI TRASMISSIONE	
LEVE DEL CAMBIO	Shimano Deore
DERAGLIATORE	MRP 1X CS custom
CAMBIO	Shimano Deore, 10-Speed, Shadow+
FRENI	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Tektro HD-M745 Orion
PACCO PIGNONI	Shimano CS-M4100-10, 11-46T, 10-Speed
CATENA	KMC e.10 Sport, e-bike optimized
GUARNITURA	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)
DROP MOVIMENTO CENTRALE	N/A
RUOTE	
CERCHI	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
MOZZI	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
RAGGI	Stainless Steel
COPERTURE	Maxxis Rekon 29x2.4" foldable, 60tpi, EXO, Tubeless Ready
EXTRA	Giant EnergyPak 6A Smart charger

## CARATTERISTICHE

- Telaio: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Forcella: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
- Leve del cambio: Shimano Deore
- Guarnitura: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)
- Colorazioni: Balsam Green

**Prezzo: € 3.299,00**

## GEOMETRIA

TELAIO	S	M	L	XL
Lunghezza tubo sella (mm)	406	432	482	507
Angolo tubo sella	73,5°	73,5°	73,5°	73,5°
Lunghezza tubo orizzontale (mm)	580	600	625	650
Lunghezza tubo sterzo (mm)	100	110	120	135
Angolo sterzo	67,0°	67,0°	67,0°	67,0°
Rake forcella (mm)	40	40	40	40
Trail (mm)	113,6	113,6	113,6	113,6
Interasse (mm)	1166	1187	1213	1240
Lunghezza carro posteriore (mm)	475	475	475	475
Drop movimento centrale (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Altezza stand over (mm)	741	756	788	792
Larghezza manubrio c/c (mm)	780	780	780	780
Lunghezza attacco manubrio (mm)	40	40	50	50
Lunghezza pedivella (mm)	160	160	165	165
Dimensione e ruote	29"	29"	29"	29"

*Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.*